

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Professional® Water Sealant <100 VOC  
Product form : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Water Repellent  
Other information : For professional use only

#### 1.3. Details of the supplier of the safety data sheet

4456 S. Clifton  
Wichita, Kansas 67216  
1-800-676-7346

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 3 H226  
Skin Sens. 1 H317  
Aquatic Chronic 2 H411

*This product also contains more than 0.1% of a component that has been found to be classified as a Carcinogen 2 according to CLP Annex VI (EC No 1272/2008)*

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Warning**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing fume, mist, vapours  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P273 - Avoid release to the environment  
P280 - Wear eye protection, face protection, protective clothing, protective gloves  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P321 - Specific treatment (see first aid instructions on this label)  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, dry sand, foam to extinguish  
P391 - Collect spillage  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

# Professional® Water Sealant <100 VOC

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%
4-chlorobenzotrifluoride	(CAS No) 98-56-6	60 - 100
Proprietary ingredient 1	Proprietary*	0.1 - 1
Proprietary ingredient 2	Proprietary*	0.1 - 1

\*In accordance with paragraph (j) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity has been withheld as a trade secret

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause an allergic skin reaction.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : May cause skin irritation.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation.
- Chronic symptoms : Skin sensitization.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Dry powder. Water spray. Sand.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid. May be ignited by heat, sparks or flames.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

- Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

# Professional® Water Sealant <100 VOC

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Place in properly labeled metal container.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in properly labeled metal container. This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

See Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep away from ignition sources.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Proprietary ingredient 1	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Proprietary ingredient 2	
ACGIH TWA (ppm)	50
ACGIH STEL (ppm)	100
OSHA PEL (TWA) (mg/m <sup>3</sup> )	525
OSHA PEL (TWA) (ppm)	100
4-chlorobenzotrifluoride (98-56-6)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

### 8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Gloves. Protective goggles. Protective clothing.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

# Professional® Water Sealant <100 VOC

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Clear. Colorless.
Odor	: Naphthalene-like.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: 0.9
Melting point	: -36 °C (- 33 °F)
Freezing point	: No data available
Boiling point	: 139 °C (282 °F)
Flash point	: 39 °C (103 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 5.3 mm Hg (20 °C)
Relative vapour density at 20 °C	: 6.2
Relative density	: 1.34
Density	: 1342 g/l (11.2 lbs/gal)
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Ignition sources. Open flame. Elevated temperatures.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

None known.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Proprietary ingredient 1	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	0.2 mg/kg
LC50 inhalation rat (mg/l)	20 mg/l/4h
Proprietary ingredient 2	
LD50 oral rat	> 1600 mg/kg
4-chlorobenzotrifluoride (98-56-6)	
LD50 oral rat	13 g/kg

# Professional® Water Sealant <100 VOC

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-chlorobenzotrifluoride (98-56-6)	
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat (mg/l)	33 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: Skin sensitization.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

Professional® Water Sealant <100 VOC	
Persistence and degradability	No information available.

#### 12.3. Bioaccumulative potential

Professional® Water Sealant <100 VOC	
Bioaccumulative potential	No information available.

#### 12.4. Mobility in soil

Professional® Water Sealant <100 VOC	
Ecology - soil	No information available.

#### 12.5. Other adverse effects

Other adverse effects : No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

#### In accordance with DOT

Not hazardous for transport

#### Transport by sea

UN-No. (IMDG)	: UN 2234 Chlorobenzotrifluorides
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Subsidiary risk (IMDG)	: 9

#### Air transport

UN-No.(IATA)	: UN2234 Chlorobenzotrifluorides
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

# Professional® Water Sealant <100 VOC

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Subsidiary risk (IATA) : 9

### Additional information

Other information

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Professional® Water Sealant &lt;100 VOC</b>	
All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
<b>Acetic anhydride (108-24-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
<b>n-Amyl acetate (628-63-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

<b>Benzene (71-43-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	NA


#### Silica, amorphous (7631-86-9)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.  
Revision date : 02/19/2015  
Other information : Author: CJS.

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.  
NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

Health : 1\*  
Flammability : 2  
Physical : 1  
Personal Protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product