

4456 S Clifton Avenue
Wichita, KS 67216
800 676-7346

Phase II Cleaner

PRODUCT DESCRIPTION & USE

Composition and Materials:

Phase II Cleaner is an ecologically acceptable graffiti remover designed to work best when used in conjunction with Professional® Water Sealant Anti-Graffiti.

Phase II Cleaner is biodegradable and environmentally safe. Does not contain methylenechloride, MEK or caustics. It has a citrus aroma.

INSTALLATION

Surface & Air Temperatures

Product efficiency is reduced below 40°F. Always apply to an inconspicuous area prior to use.

Application

Phase II Cleaner can be applied directly to graffiti with a low pressure sprayer. Allow Professional Phase II Cleaner to work for 5 to 10 minutes. Agitate hard to clean areas (small crevices, holes, and grooves) with a stiff bristle brush to help remove graffiti. Spray surface with water using a hose or power washer. Power washer not to exceed 1500 p.s.i .

Precautions

Use of any other cleaner to remove graffiti from surfaces treated with Professional® Water Sealant & Anti-Graffiti may reduce the effectiveness of the non-sacrificial graffiti protection.

CLEAN UP & STORAGE

Collect and dispose of residue in compliance with local, state and federal regulations. In many cities, waste can be disposed of directly to the sewer after the removal of oils and contaminants. Check with local authorities to ensure compliance.

Shelf life is 2 years. Store in a cool place.

SAFETY INFORMATION

FIRST AID

Inhalation

Avoid excessive exposure and breathing of vapor. Avoid contact with skin or clothing. Wash thoroughly after handling. Keep away from heat and ignition sources. Wear protective gloves and goggles during application.

Remove to fresh air. Contact physician.

Skin

Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water. Wash clothing before reuse.

Eyes

Flush eyes with water for 15 minutes. Contact Physician.

Ingestion

DO NOT INDUCE VOMITING. Contact Physician.

TECHNICAL SERVICES

Technical services and samples are available upon request. Services include assistance during design, specification, and application stages. Please call 800-676-7346 for assistance.