

Extra Resource Questions

Question:	Answer:
Can I apply the product with a car paint spray gun?	No. This atomizes the product instead of flood coat with rundown.
What kind of sprayer should I use?	A high volume low pressure sprayer such as a normal garden sprayer with chemical resistant fittings.
Can I use a brush instead of a sprayer?	Yes. Use of a solvent resistant, natural bristle or foam brush is only recommended in areas where spray application is not practical. Spray provides the most uniform application.
Can I use a roller instead of a sprayer?	Yes. Use of a solvent resistant thick nap roller is only recommended in areas where spray application is not practical. Spray provides the most uniform application.
Can I apply the product on a basement floor	No. Below grade applications are not supported due to hydrostatic pressure.
What is a chemical resistant sprayer or chemical resistant fittings?	Any home improvement store and many online stores sell these. Look for a pump-up garden sprayer with viton gaskets and a brass spray tip. Use a fan tip for better coverage.
What do I do if there are deep rakes in the mortar?	Product can pool in deep raked ledges and run down in thin streams on a vertical surface after the face of the block has partially dried, creating dark thin streaks. Brush pooled product off ridges within about ten minutes.
What is the curing time for graffiti applications?	Ten days curing is needed to provide full protection from paint. It may take longer in cold temperatures.
What is the curing time for water sealant applications?	The product is dry to touch in about 2 hours, walk on in about 24 hours, and drive on in about 72 hours. An initial water barrier is created in 12-24 hours with a full cure in about 14 days.
Can I apply the product when the temperature is below freezing?	Yes, but be sure substrate is dry. Product cures more slowly under 40 degrees.
How do I know the substrate is dry?	If you have a moisture meter, it should read below 15%. Alternatively, tape a one-foot square of plastic on the substrate overnight. If there is condensation under the plastic in the morning, it is too wet for application.
Can I apply the product for Anti-graffiti on horizontal surfaces?	Our anti-graffiti application is not recommended for horizontal surfaces. Small ledges that will not be walked on are ok.
What to do if your sprayer is clogging?	Remove the filters in the tank and spray head if they are present. Clean the nozzle with mineral spirits.

Can I use a stream spray tip on a sprayer?	No. A stream tip will not evenly saturate the surface and will end up looking streaky. Use a fan tip on the sprayer.
Can your product bridge hairline cracks?	Yes. Our silicone rubber elongates up to 400% and can bridge hairline cracks? We define a hairline crack as one that cannot be seen from about six feet away.
Can you apply the product in a below grade area like a basement?	No. Our product is not suitable for below grade applications.
Can I apply your product over silicone caulk?	Yes.
Can I apply your product over a caulk that is not silicone?	Using silicone caulk is recommended in order to ensure you get a good bond with RTV Silicone. If you are using a caulk other than silicone, check with the manufacturing to ensure RTV Silicone can bond with it.